



AM Deactivator

The Deactivator provides convenient and simple deactivation for even the smallest checkstand areas. Designed in front-end applications where high-speed throughput is not a priority, this unit deactivates active AM EAS labels up to 10.16cm (4in) above the surface of the pad at a throughput speed of up to 142cm/sec. (56in/sec). An LED light on the deactivator provides visual deactivation notification. Optional Remote Alarm Module provides visual and audible confirmations when active labels are detected and deactivated. The locking key feature within the remote alarm module prevents unauthorized use of the CompactPad when point-of-sale is unattended. The alarm module can be mounted almost anywhere on the checkstand.

When connected to a compatible EAS data management device, real-time deactivation counts can be generated into user-friendly customizable reports to provide business-critical data.

Retailer Values

- // Designed for even the smallest checkstand areas to allow maximum use of counter space
- // Reliable deactivation for increased customer service and fewer nuisance alarms
- // EAS connectivity option allows generation of operational information to help quickly identify and correct performance issues
- // Built-in audible and visual indicators provide immediate feedback when active labels are detected and deactivated, enhancing front-end productivity

Product Code

F05000201

Product Compatibility

All AM EAS Labels
Wireless Device Manager

Specifications

Length	32.5cm (12.8in)
Width	11.22in 28.5cm
Height	13cm (5.12in)
Weight	2.18kg (4.8lbs)

Electrical

Requires Universal Controller
(ZBAMB9010-IPS)

Environmental Constraints

Operating Frequency

58 kHz

Operating Temperature

0°C to 40°C (32°F to 104°F)

AM Deactivator

